MATHEMATICS (US)   **9280/04**

Paper 4 Mechanics 1 **(M1)**   **For Examination from 2013**

SPECIMEN MARK SCHEME

1 hour 15 minutes

MAXIMUM MARK: 50

This document consists of **5** printed pages and **1** blank page.

[Turn over

Mark Scheme Notes

Marks are of the following three types:

M   Method mark, awarded for a valid method applied to the problem. Method marks are not lost for numerical errors, algebraic slips, or errors in units. However, it is not usually sufficient for a candidate just to indicate an intention of using some method or just to quote a formula; the formula or idea must be applied to the specific problem in hand, e.g., by substituting the relevant quantities into the formula. Correct application of a formula without the formula being quoted obviously earns the M mark and in some cases an M mark can be implied from a correct answer.

A   Accuracy mark, awarded for a correct answer or intermediate step correctly obtained. Accuracy marks cannot be given unless the associated method mark is earned (or implied).

B   Mark for a correct result or statement independent of method marks.

- When a part of a question has two or more "method" steps, the M marks are generally independent unless the scheme specifically says otherwise; and similarly when there are several B marks allocated. The notation DM or DB (or dep*) is used to indicate that a particular M or B mark is dependent on an earlier M or B (asterisked) mark in the scheme. When two or more steps are run together by the candidate, the earlier marks are implied and full credit is given.

- The symbol √ implies that the A or B mark indicated is allowed for work correctly following on from previously incorrect results. Otherwise, A or B marks are given for correct work only. A and B marks are not given for fortuitously "correct" answers or results obtained from incorrect working.

- Note: B2 or A2 means that the candidate can earn 2 or 0.
  B2/1/0 means that the candidate can earn anything from 0 to 2.

  The marks indicated in the scheme may not be subdivided. If there is genuine doubt whether a candidate has earned a mark, allow the candidate the benefit of the doubt. Unless otherwise indicated, marks once gained cannot subsequently be lost, e.g., wrong working following a correct form of answer is ignored.

- Wrong or missing units in an answer should not lead to the loss of a mark unless the scheme specifically indicates otherwise.

- For a numerical answer, allow the A or B mark if a value is obtained that is correct to 3 s.f., or that would be correct to 3 s.f. if rounded (1 d.p. in the case of an angle). As stated above, an A or B mark is not given if a correct numerical answer arises fortuitously from incorrect working. For Mechanics questions, allow A or B marks for correct answers that arise from taking g equal to 9.8 or 9.81 instead of 10.

The following abbreviations may be used in a mark scheme or used on the scripts:

AEF   Any Equivalent Form (of answer is equally acceptable)

AG   Answer Given on the question paper (so extra checking is needed to ensure that the detailed working leading to the result is valid)

BOD   Benefit of Doubt (allowed when the validity of a solution may not be absolutely clear)

CAO   Correct Answer Only (emphasizing that no "follow through" from a previous error is allowed)

CWO   Correct Working Only often written by a "fortuitous" answer

ISW   Ignore Subsequent Working

MR   Misread

PA   Premature Approximation (resulting in basically correct work that is insufficiently accurate)

SOS   See Other Solution (the candidate makes a better attempt at the same question)

SR   Special Ruling (detailing the mark to be given for a specific wrong solution, or a case where some standard marking practice is to be varied in the light of a particular circumstance)

Penalties

MR –1   A penalty of MR –1 is deducted from A or B marks when the data of a question or part question are genuinely misread and the object and difficulty of the question remain unaltered. In this case all A and B marks then become "follow through √" marks. MR is not applied when the candidate misreads their own figures – this is regarded as an error in accuracy. An MR –2 penalty may be applied in particular cases if agreed at the coordination meeting.

PA –1   This is deducted from A or B marks in the case of premature approximation. The PA –1 penalty is usually discussed at the meeting.

[Turn over

1	(i)	[DF – 600 = 700 × 2]	M1		For using Newton's second l... needed)
		Driving force is 2000 N	A1	**[2]**	
	(ii)	[P = 2000 × 15]	M1		For using P = Fv
		Rate of working is 30000 W (or 30 kW)	A1√	**[2]**	
2	(i)	Gain in PE = 1250g × 1.54 (= 19250 J)	B1		
		[WD = 1250g × 1.54 + 5750]	M1		For using WD by crane = Gain in PE + WD against resistance
		Work done is 25000 J (or 25 kJ)	A1	**[3]**	
	(ii)	[1250 = 25000 / T]	M1		for using P = Δ(WD) / Δt
		Time is 20 s	A1√	**[2]**	Ans**(i)** ÷ 1250
3			M1		For resolving forces horizontally or vertically (3 terms needed)
		$T\cos\theta + T\sin\theta = 15.5$	A1		AEF
		$-T\cos\theta + T\sin\theta = 8.5$	A1		AEF
			DM1		For solving for $T\sin\theta$ and $T\cos\theta$
		$T\sin\theta = 12$ and $T\cos\theta = 3.5$	A1		AG
		$\theta = 73.7°$ (or 1.29 radians)	B1	**[6]**	
4	(i)		M1		For resolving forces parallel to the plane (either case) – 3 terms needed
		$2X + F = 11g\sin30°$ and $9X - F = 11g\sin30°$	A1		
		X = 10	A1	**[3]**	
	(ii)	F = 35	B1		May be implied.
		$R = 11g\cos30°$	B1		
			DM1		For using $\mu = F/R$
		Coefficient is 0.367	A1√	**[4]**	
5	(i)	v(600) = 0.025 × 600	B1		
			M1		For using $0 = v(600 + 2600) - 0.0375t_3$ and $v(600 + 2600) = v(600)$
		$0 = 15 - 0.0375t_3$	A1		
		Total time is 3600 s	A1	**[4]**	
	(ii)	For correct graph	M1		Shape only
		[d = ½ (2600 + 3600) × 15 or d = ½ 0.025 × 600² + 2600 × 15 + ½ 0.0375 × 400²]	A1√		For method of finding distance
		Distance is 46500	A1√	**[3]**	
	(iii)	Values of t are 300 and 3400	B1	**[1]**	

6	(i)		M1		For using s = $\int v \, dt$
		$s = 2t^2 - t^4/64 \; (+ \, C)$	A1		
		$[t^4 - 128t^2 + 64^2 = 0]$	M1		For attempting to solve s(t) = 64
		$(t^2 - 64)^2 = 0$	A1		
		Time taken is 8 s	A1	**[5]**	
	(ii)		M1		For using a = dv/dt
		$a = 4 - 3t^2/16$	A1		
		a is positive for $0 < t < \dfrac{8}{\sqrt{3}}$ or $0 < t < 4.62$	B2	**[4]**	SR: Allow B1 for $t < \dfrac{8}{\sqrt{3}}$ SR: B1 for $0 \le t \le \dfrac{8}{\sqrt{3}}$ or 4.62
7	(i)		M1		For applying Newton's second law to A or to B
		$T - 12 = 1.2a$ and $20 - T = 2a$	A1		Accept $(2 - 1.2)g = (2.0 + 1.2)a$ as an alternative for one of these equations
		Acceleration is 2.5 ms^{-2}	B1		
		Tension is 15 N	A1	**[4]**	
	(ii) **(a)**	PE gain = $12 \times 1.5 = 18$ J	B1		
	(b)	WD on A = $15 \times 1.5 = 22.5$J	B1		
	(c)	Gain in KE = ans**(b)** – ans**(a)** = 4.5 J	B1√	**[3]**	alt: KE = $\frac{1}{2}$ 1.2(2 × 2.5 × 1.5) = 4.5J
	(iii)	$v = 1.6 \times 2.5$	B1√		
			M1		For using v = u – gt
		t = 0.4 s	A1		May be implied
		Total time taken is 0.8 s	A1	**[4]**	

[Turn over

BLANK PAGE