

MARK SCHEME for the May/June 2007 question paper

9702 PHYSICS

9702/04

Paper 4 (A2 Structures Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began.

All Examiners are instructed that alternative correct answers and unexpected approaches in candidates' scripts must be given marks that fairly reflect the relevant knowledge and skills demonstrated.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- CIE will not enter into discussions or correspondence in connection with these mark schemes.

CIE is publishing the mark schemes for the May/June 2007 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.

Page 2	Mark Scheme	Syllabus	Number
	GCE A/AS LEVEL – May/June 2007	9702	

- 1 (a) (region of space) where a mass experiences a force B1
- (b) (i) potential energy = $(-)\frac{GMm}{x}$ C1
 $\Delta E_p = \frac{GMm}{2R} - \frac{GMm}{3R}$ M1
 $= \frac{GMm}{6R}$ A0 [2]
- (ii) $E_k = \frac{1}{2}m(7600^2 - 7320^2)$ M1
 $= (2.09 \times 10^6)m$ A0 [1]
- (c) (i) $2.09 \times 10^6 = \frac{(6.67 \times 10^{-11} M)(6 \times 3.4 \times 10^6)}{}$ C1
 $M = 6.39 \times 10^{23} \text{ kg}$ A1 [2]
- (ii) e.g. no energy dissipated due to friction with atmosphere/air
rocket is outside atmosphere
not influenced by another planet etc. B1 [1]
- 2 (a) (on melting,) bonds between molecules are broken/weakened B1
or molecules further apart/are able to slide over one another B1
kinetic energy unchanged so no temperature change B1 [3]
potential energy increased/changed so energy required
- (b) thermal energy/heat required to convert unit mass of solid to liquid M1
with no change in temperature/ at its normal boiling point A1 [2]
- (c) (i) thermal energy lost by water = $0.16 \times 4.2 \times 100$
 $= 67.2 \text{ kJ}$ C1
 $67.2 = 0.205 \times L$ C1
 $L = 328 \text{ kJ kg}^{-1}$ A1 [3]
- (ii) more energy (than calculated) melts ice M1
so, (calculated) L is lower than the accepted value A1 [2]
- 3 (a) field strength = potential gradient M1
correct sign OR directions discussed A1 [2]
- (b) area is $21.2 \text{ cm}^2 \pm 0.4 \text{ cm}^2$ C2
(if outside $\pm 0.4 \text{ cm}^2$ but within $\pm 0.8 \text{ cm}^2$, allow 1 mark)
 1.0 cm^2 represents $(1.0 \times 10^{-2} \times 2.5 \times 10^3 =) 25 \text{ V}$ C1
potential difference = 530 V A1 [4]
- (c) $\frac{1}{2}mv^2 = qV$
 $\frac{1}{2} \times 9.1 \times 10^{-31} \times v^2 = 1.6 \times 10^{-19} \times 530$ C1
 $v = 1.37 \times 10^7 \text{ ms}^{-1}$ A1 [2]
- (d) (i) $d = 0$ B1 [1]
- (ii) acceleration decreases then increases B1
some quantitative analysis (e.g. minimum at 4.0 cm) B1 [2]
(any suggestion that acceleration becomes zero or that there is a deceleration scores 0/2)

Page 3	Mark Scheme	Syllabus	er
	GCE A/AS LEVEL – May/June 2007	9702	

- 4 (a) r.m.s. output = $9/\sqrt{2}$ or peak input = $230\sqrt{2}$
 $N_S/N_P = V_S/V_P$
 $N_S = 138 \rightarrow 140$ turns
- (b) (i) four diodes correctly positioned regardless of output polarity giving correct output polarity (*all 'point to left'*)
- (ii) capacitor shown in parallel with R
- (c) (i) time t_1 to time t_2
- (ii) sketch: same peak values
 ripple reduced and reasonable shape
- 5 (a) (i) packet/discrete quantity/quantum (of energy) of e.m. radiation
- (ii) either $E = (6.63 \times 10^{-34} \times 3 \times 10^8)/(350 \times 10^{-9})$
 or $E = (6.63 \times 10^{-34} \times 8.57 \times 10^{14})$
 $E = 5.68 \times 10^{-19}$ J
- (iii) 0.5
- (b) (i) energy of photon
 to cause emission of electron from surface
either with zero k.e *or* photon energy is minimum
- (ii) correct conversion eV \rightarrow J or J \rightarrow eV seen once
 photon energy must be greater than work function
 350 nm wavelength and potassium metal
- 6 (a) probability of decay
 of a nucleus per unit time
 (*allow 1 mark for $A = \lambda N$, with symbols explained*)
- (b) (i) $\lambda = \ln 2/(28 \times 365 \times 24 \times 3600)$
 $= 7.85 \times 10^{-10} \text{ s}^{-1}$
- (ii) $A = (-)\lambda N$
 $N = (6.4 \times 10^9)/(7.85 \times 10^{-10})$
 $= 8.15 \times 10^{18}$
 mass = $(8.15 \times 10^{18} \times 90)/(6.02 \times 10^{23})$ (e.c.f. for value of N)
 $= 1.22 \times 10^{-3}$ g
- (iii) volume = $(1.22 \times 10^{-3}/2.54 =) 4.8 \times 10^{-4} \text{ cm}^3$
- (c) *either* very small volume of Strontium-90 has high activity
or dust can be highly radioactive
 breathing in dust presents health hazard

Page 4	Mark Scheme	Syllabus	er
	GCE A/AS LEVEL – May/June 2007	9702	

- 7 (a) (i) oscillations are damped/amplitude decreases
as magnet moves, flux is cut by coil
e.m.f./current is induced in the coil
causing energy loss in load OR force on magnet
energy is derived from oscillations of magnet
OR force opposes motion of magnet
- (ii) $T = 0.60 \text{ s}$
 $\omega_0 (= 2\pi/T) = 10.5 \text{ rad s}^{-1}$
- (b) sketch: sinusoidal wave with period unchanged or slightly smaller
same initial displacement, less damping
- (c) (i) sketch: general shape – peaked curve
peak at ω_0 and amplitude never zero
- (ii) resonance
- (iii) useful: e.g. child on swing, microwave oven heating
avoid: e.g. vibrating panels, vibrating bridges
(for credit, stated example must be put in context)

Section B

- 8 (a) e.g. infinite (voltage) gain
infinite input impedance
zero output impedance
infinite bandwidth
infinite slew rate
(any three, 1 each)
- (b) (i) negative (feedback)
- (ii) 1 gain $(= 5.8/0.069) = 84$
- (ii) 2 gain $= 1 + 120/X$
 $84 = 1 + 120/X$
 $X = 1.45 \text{ k}\Omega$
- (iii) gain increases OR bandwidth reduced OR output increases

Page 5	Mark Scheme	Syllabus	er
	GCE A/AS LEVEL – May/June 2007	9702	

- 9 (a)** X-ray beam directed through body onto detector (plate)
different tissues absorb/attenuate beam by different amounts
giving 'shadow' image of structures
any other detail e.g. comment re sharpness or contrast
- (b)** X-ray image is flat OR 2-dimensional (1)
CT scan takes many images of a slice at different angles (1)
these build up an image of a slice through the body (1)
series of images of slices is made (1)
so that 3D image can be built up (1)
image can then be rotated (1)
1 mark for each point, max 5
- 10 (a)** correct values of 2, 5, 10, 15 and 4 (*-1 each error*)
graph drawn as a series of steps
steps occurring at correct times
- (b)** sample more frequently
greater number of bits
- 11 (a)** modulator and oscillator identified
both amplifiers identified correctly
ADC and parallel-to serial converter identified
- (b)** computer at cellular exchange
monitors signal strength
switches call from one base station to another
to maintain maximum signal strength

B1
B1
B1
B1

B5 [5]

B2
M1
A1 [4]

B1
B1 [2]

B1
B1
B1 [3]

B1
B1
B1
B1 [4]