

**MARK SCHEME for the May/June 2011 question paper  
for the guidance of teachers**

**9702 PHYSICS**

**9702/41**

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2011 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.

Page 2	Mark Scheme: Teachers' version	Syllabus
	GCE AS/A LEVEL – May/June 2011	9702

### Section A

- 1 (a) (i) force proportional to product of masses B1  
force inversely proportional to square of separation B1
- (ii) separation much greater than radius / diameter of Sun / planet B1 [1]
- (b) (i) e.g. force or field strength  $\propto 1 / r^2$   
potential  $\propto 1 / r$  B1 [1]
- (ii) e.g. gravitational force (always) attractive B1  
electric force attractive or repulsive B1 [2]
- 2 (a) number of atoms of carbon-12 M1  
in 0.012 kg of carbon-12 A1 [2]
- (b)  $pV = NkT$  or  $pV = nRT$  C1  
substitutes temperature as 298K C1  
*either*  $1.1 \times 10^5 \times 6.5 \times 10^{-2} = N \times 1.38 \times 10^{-23} \times 298$   
*or*  $1.1 \times 10^5 \times 6.5 \times 10^{-2} = n \times 8.31 \times 298$  and  $n = N / 6.02 \times 10^{23}$  C1  
 $N = 1.7 \times 10^{24}$  A1 [4]
- 3 (a) acceleration / force proportional to displacement from a fixed point M1  
acceleration / force (always) directed towards that fixed point / in opposite  
direction to displacement A1 [2]
- (b) (i)  $A\rho g / m$  is a constant and so acceleration proportional to  $x$  B1  
negative sign shows acceleration towards a fixed point / in opposite  
direction to displacement B1 [2]
- (ii)  $\omega^2 = (A\rho g / m)$  C1  
 $\omega = 2\pi f$  C1  
 $(2 \times \pi \times 1.5)^2 = ((4.5 \times 10^{-4} \times 1.0 \times 10^3 \times 9.81) / m)$  C1  
 $m = 50\text{g}$  A1 [4]
- 4 (a) work done in bringing unit positive charge M1  
from infinity (to that point) A1 [2]
- (b) (i) field strength is potential gradient B1 [1]
- (ii) field strength proportional to force (on particle Q) B1  
potential gradient proportional to gradient of (potential energy) graph B1  
so force is proportional to the gradient of the graph A0 [2]

Page 3	Mark Scheme: Teachers' version	Syllabus
	GCE AS/A LEVEL – May/June 2011	9702

- (c) energy =  $5.1 \times 1.6 \times 10^{-19}$  (J)  
 potential energy =  $Q_1Q_2 / 4\pi\epsilon_0r$   
 $5.1 \times 1.6 \times 10^{-19} = (1.6 \times 10^{-19})^2 / 4\pi \times 8.85 \times 10^{-12} \times r$   
 $r = 2.8 \times 10^{-10}$  m
- (d) (i) work is got out as x decreases  
 so opposite sign
- (ii) energy would be doubled  
 gradient would be increased
- 5 (a) region (of space) where there is a force  
*either* on / produced by magnetic pole  
*or* on / produced by current carrying conductor / moving charge
- (b) (i) force on particle is (always) normal to velocity / direction of travel  
 speed of particle is constant
- (ii) magnetic force provides the centripetal force  
 $mv^2 / r = Bqv$   
 $r = mv / Bq$
- (c) (i) direction from 'bottom to top' of diagram
- (ii) radius proportional to momentum  
 ratio =  $5.7 / 7.4$   
 = 0.77  
*(answer must be consistent with direction given in (c)(i))*
- 6 (a) (i) to concentrate the (magnetic) flux / reduce flux losses
- (ii) changing flux (in core) induces current in core  
 currents in core give rise to a heating effect
- (b) (i) e.m.f. induced proportional to  
 rate of change of (magnetic) flux (linkage)
- (ii) magnetic flux in phase with / proportional to e.m.f. / current in primary coil  
 e.m.f. / p.d. across secondary proportional to rate of change of flux  
 so e.m.f. of supply not in phase with p.d. across secondary
- (c) (i) for same power (transmission), high voltage with low current  
 with low current, less energy losses in transmission cables
- (ii) voltage is easily / efficiently changed

Page 4	Mark Scheme: Teachers' version	Syllabus
	GCE AS/A LEVEL – May/June 2011	9702

- 7 (a) for a wave, electron can 'collect' energy continuously B  
 for a wave, electron will always be emitted / M1  
 electron will be emitted at all frequencies..... A1  
 after a sufficiently long delay
- (b) (i) *either* wavelength is longer than threshold wavelength B1 [1]  
*or* frequency is below the threshold frequency  
*or* photon energy is less than work function
- (ii)  $hc / \lambda = \phi + E_{MAX}$  C1  
 $(6.63 \times 10^{-34} \times 3.0 \times 10^8) / (240 \times 10^{-9}) = \phi + 4.44 \times 10^{-19}$  C1  
 $\phi = 3.8 \times 10^{-19} \text{ J (allow } 3.9 \times 10^{-19} \text{ J)}$  A1 [3]
- (c) (i) photon energy larger M1  
 so (maximum) kinetic energy is larger A1 [2]
- (ii) fewer photons (per unit time) M1  
 so (maximum) current is smaller A1 [2]
- 8 (a) (i) Fe shown near peak A1 [1]  
 (ii) Zr shown about half-way along plateau A1 [1]  
 (iii) H shown at less than 0.4 of maximum height A1 [1]
- (b) (i) heavy / large nucleus breaks up / splits M1  
 into two nuclei / fragments of approximately equal mass A1 [2]
- (ii) binding energy of nucleus =  $B_E \times A$  B1  
 binding energy of parent nucleus is less than sum of binding energies B1 [2]  
 of fragments

**Section B**

- 9 (a) to compare two potentials / voltages M1  
output depends upon which is greater A1
- (b) (i) resistance of thermistor = 2.5 k $\Omega$  C1  
resistance of X = 2.5 k $\Omega$  A1 [2]
- (ii) at 5 °C / at < 10 °C,  $V^- > V^+$  M1  
so  $V_{OUT}$  is -9V A1  
at 20 °C / at > 10 °C,  $V^- < V^+$  and  $V_{OUT}$  is +9V B1  
 $V_{OUT}$  switches between negative and positive at 10 °C B1 [4]  
(allow similar scheme if 20 °C treated first)
- 10 (a) product of density (of medium) and speed of sound (in the medium) B1 [1]
- (b)  $\alpha$  would be nearly equal to 1 M1  
*either* reflected intensity would be nearly equal to incident intensity  
*or* coefficient for transmitted intensity =  $(1 - \alpha)$  M1  
transmitted intensity would be small A1 [3]
- (c) (i)  $\alpha = (1.7 - 1.3)^2 / (1.7 + 1.3)^2$  C1  
 $= 0.018$  A1 [2]
- (ii) attenuation in fat =  $\exp(-48 \times 2x \times 10^{-2})$  C1  
 $0.012 = 0.018 \exp(-48 \times 2x \times 10^{-2})$  C1  
 $x = 0.42$  cm A1 [3]
- 11 (a) frequency of carrier wave varies M1  
(in synchrony) with the displacement of the information signal A1 [2]
- (b) (i) 5.0V A1 [1]  
(ii) 640 kHz A1 [1]  
(iii) 560 kHz A1 [1]  
(iv) 7000 (*condone unit*) A1 [1]
- 12 (a) e.g. acts as 'return' for the signal M1  
shields inner core from noise / interference / cross-talk A1 [2]  
(any two sensible answers, 1 each, max 2) B2 [2]
- (b) e.g. greater bandwidth  
less attenuation (per unit length)  
less noise / interference  
(any two sensible answers, 1 each, max 2) B2 [2]
- (c) attenuation is 2.4 dB C1  
attenuation =  $10 \lg(P_1/P_2)$  C1  
ratio = 1.7 A1 [3]