

**MARK SCHEME for the October/November 2012 series**

**9702 PHYSICS**

**9702/21**

Paper 2 (AS Structured Questions), maximum raw mark 60

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the October/November 2012 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

Page 2	Mark Scheme	Syllabus
	GCE AS/A LEVEL – October/November 2012	9702

- 1 (a) (i) acceleration = change in velocity / time (taken)  
or acceleration = rate of change of velocity B1
- (ii) a body continues at constant velocity unless acted on by a resultant force B1
- (b) (i) distance is represented by the area under graph C1  
distance =  $\frac{1}{2} \times 29.5 \times 3 = 44.3 \text{ m}$  (accept 43.5 m for 29 to 45 m for 30) A1 [2]
- (ii) resultant force = weight – frictional force B1  
frictional force increases with speed B1  
at start frictional force = 0 / at end weight = frictional force B1 [3]
- (iii) 1. frictional force increases B1 [1]  
2. frictional force (constant) and then decreases B1 [1]
- (iv) 1. acceleration =  $(v_2 - v_1) / t = (20 - 50) / (17 - 15)$  C1  
=  $(-15 \text{ m s}^{-2})$  A1 [2]  
2.  $W - F = ma$  C1  
 $W = 95 \times 9.81 (= 932)$  C1  
 $F = (95 \times 15) + 932 = 2400 (2360) (2357) \text{ N}$  A1 [3]
- 2 (a) resistance = potential difference / current B1 [1]
- (b) (i) metal wire in series with power supply and ammeter B1  
voltmeter in parallel with metal wire B1  
rheostat in series with power supply or potential divider arrangement  
or variable power supply B1 [3]
- (ii) 1. intercept on graph B1 [1]  
2. scatter of readings about the best fit line B1 [1]
- (iii) correction for zero error explained B1  
use of  $V$  and corrected  $I$  values from graph C1  
resistance =  $V/I = 22.(2) \Omega$  [e.g. 4.0 / 0.18] A1 [3]
- (c)  $R = 6.8 / 0.64 = 10.625$  C1  
 $\%R = \%V + \%I$   
 $= (0.1 / 6.8) \times 100 + (0.01 / 0.64) \times 100$  C1  
 $= 1.47\% + 1.56\%$   
 $\Delta R = 0.0303 \times 10.625 = 0.32 \Omega$   
 $R = 10.6 \pm 0.3 \Omega$  A1 [3]

Page 3	Mark Scheme	Syllabus
	GCE AS/A LEVEL – October/November 2012	9702

- 3 (a) pressure = force / area
- (b) molecules collide with object / surface and rebound B1  
 molecules have change in momentum hence force acts B1  
 fewer molecules per unit volume on top of mountain / temperature is less  
 hence lower speed of molecules B1  
 hence less pressure A0 [3]
- (c) (i)  $\rho = m / V$  C1  
 $W = V\rho g = 0.25 \times 0.45 \times 9.81 \times 13600$  C1  
 $= 15000$  (15009)N A1 [3]
- (ii)  $p = W / A$  (or using  $p = \rho gh$ ) = 15009 / 0.45  
 $= 3.3 \times 10^4$  Pa A1 [1]
- (iii) pressure will be greater due to the air pressure (acting on the surface of the liquid) B1 [1]
- 4 (a) waves pass through the elements / gaps / slits in the grating M1  
 spread into geometric shadow A1 [2]
- (b) (i) 1. displacements add to give resultant displacement B1  
 each wavelength travels the same path difference or are in phase B1  
 hence produce a maximum A0 [2]
2. to obtain a maximum the path difference must be  $\lambda$  or phase difference  
 $360^\circ / 2\pi$  rad B1  
 $\lambda$  of red and blue are different B1  
 hence maxima at different angles / positions A0 [2]
- (ii)  $n\lambda = d \sin \theta$  C1  
 $N = \sin 61^\circ / (2 \times 625 \times 10^{-9}) = 7.0 \times 10^5$  A1 [2]
- (iii)  $n\lambda = 2 \times 625$  is a constant (1250) C1  
 $n = 1 \rightarrow \lambda = 1250$  outside visible  
 $n = 3 \rightarrow \lambda = 417$  in visible  
 $n = 4 \rightarrow \lambda = 312.5$  outside visible  
 $\lambda = 420$  nm A1 [2]
- 5 (a) when the load is removed then the wire / body object does not return to its original shape / length B1 [1]
- (b) (i) stress = force / area C1  
 $F = 220 \times 10^6 \times 1.54 \times 10^{-6} = 340$  (338.8)N A1 [2]
- (ii)  $E = (F \times l) / (A \times e)$  C1  
 $e = (90 \times 10^6) \times 1.75 / (1.2 \times 10^{11}) = 1.31 \times 10^{-3}$  m A1 [2]
- (c) the stress is no longer proportional to the extension B1 [1]

Page 4	Mark Scheme	Syllabus
	GCE AS/A LEVEL – October/November 2012	9702

- 6 (a) 92 protons in the nucleus and 92 electrons around nucleus  
143 neutrons (in the nucleus)
- (b) (i)  $\alpha$ -particle travels short distance in air B1 [1]
- (ii) very small proportion in backwards direction / large angles B1  
majority pass through with no /small deflections B1  
either most of mass is in very small volume (nucleus) and is charged or most of atom is empty space B1 [3]
- (c)  $I = Q / t$  C1  
 $n/t = (1.5 \times 10^{-12}) / (2 \times 1.6 \times 10^{-19})$  C1  
 $n/t = 4.7 \times 10^6 \text{ s}^{-1}$  A1 [3]